



INTERNATIONAL® 3200

Product Specifications

Model Configurations	3200 4x2	Standard	Maximum
	Front GAW	8,000 lbs	8,000 lbs
	Rear GAW	13,500 lbs	15,500 lbs
	Total GVW	21,000 lbs	23,500 lbs

Wheelbase (in.)	Chassis Weights (lbs)			Dimensions (in.)				Turning Radius	
	Front	Rear	Total	Back of Cab to Rear Axle	Back of Cab to End of Frame	Center of Rear Axle to End of Frame	Over All Length	To Curb	Bumper Clearance
158	4761	2925	7686	91	170	79	277	23ft. 0in.	24ft. 2in.
169	4785	2970	7775	102	195	93	302	24ft. 5in.	25ft. 7in.
193	4902	2958	7860	126	226	100	333	27ft. 5in.	28ft. 7in.
205	4941	2994	7935	138	254	116	361	28ft. 11in.	30ft. 1in.
217	4999	2980	7979	150	270	120	377	29ft. 1in.	30ft. 3in.
254	5174	2945	8119	187	321	134	428	33ft. 6in.	34ft. 9in.

Frame Rails	50,000 PSI	10.125"
--------------------	------------	---------

Front Axle	Dana Spicer	8,000 lb Capacity
-------------------	-------------	-------------------

Front Suspension	Parabolic Taper Leaf w/ Shocks	8,000 lb Capacity
-------------------------	--------------------------------	-------------------

Brakes	Air Hydraulic Disc
---------------	-----------------------

Steering	Ross
-----------------	------

Exhaust System	Frame Mounted Horizontal Muffler Right Side w/ Right or Left Horizontal Tail Pipe
-----------------------	--

Electrical System	Leece-Neville	110, 160, 175, 200 Amp Alternators
	International	1100, 1300, 1950 CCA Battery System
	Long Life Halogen Headlights	

Front End	Tilting Fiberglass Hood w/ Three Piece Construction Chrome Grille
------------------	--



INTERNATIONAL® 3200

Product Specifications

Paint	Base Coat / Clear Coat	
Engine & Equipment	International VT365	175 HP/460 lb-ft to 215 HP/540 lb-ft
	International DT466 High Torque	230 HP/660 lb-ft
	International DT466 Standard Torque	195 HP/520 lb-ft to 215 HP/540 lb-ft
	Air Cleaner	Single Element
Transmissions	Allison	5 Speed Automatic; 2000, 2400, and MD-3060 Series
Rear Axle (Single)	International	13,500; 15,500 lb Capacity
	Dana Spicer	17,500 lb Capacity
Rear Suspension (Single)	International Air Suspension	12,000; 15,500 lb Capacity w/ 9.25" Ride Height
	Spring Suspension	13,500; 15,500 lb Capacity Vari-Rate
Fuel Tank	35 – 65 U.S. Gallons Total Capacity	Caged, Mounted Right Side or Between the Rails
Cab	Conventional Steel Cab	107.0" BBC
Interior Trim	Deluxe	
Mirrors	(02) Rectangular w/ Breakaway Type Brackets	
Driver Seats	A wide variety of seats including:	<ul style="list-style-type: none"> • Air-Suspension or Non-Suspension • High Back • Air Lumbar Support
Passenger Seats	Optional	
Front Wheels	Painted Steel, Polished Aluminum	19.5"; 8, 10 Stud
Rear Wheels	Painted Steel, Polished Aluminum	19.5"; 8, 10 Stud
Tires	Goodyear	